
HAWKER AERO

26V Portable Starting Units

Model 2680

The Hawker Aero GPU utilizes the newest technology in Lithium iron phosphate batteries. These LFP batteries have double the battery life of lead-acid batteries. This portable GPU is a 26VDC battery pack, Each GPU is suitable for the aircarft which has the protection that no more than 28.6 volts. For example, Pilatus pc6/pc12. Each GPU is suitable for the aircarft which has the protection that no more than 29.9 volts. For example, AW139, Sikorsky S-76D.

The modular design allows two GPUs to be paralleled to double the continuous output and battery capacity.





Specifications

- Peak Current
- Max continuous amps
- Nominal voltage
- Max voltage
- Amp/hour capacity
- Operating temp
- Case
- Aircraft cable
- Input voltage
- Input current
- Dimensions
- Weight
- Supplied with unit

2700A

800A5S 400A100S

DC25.6V (24V-27.8V)

DC28.3V

80Ah@10hr rate(20°C)

-30°C to +60°C(-22°F to +140°F)

Aluminum, superficial static electricity spurts

2m(6ft)with Nato connector

90-240VAC 50/60HZ

≤35A

H355L457W137mm(H14L18W5 In)

18kgs(39lbs)

Charger(90-250VAC,50/60Hz), Aircraft cable

PLEASE NOTE: Never run the batteries down below 22 volts, during a start is okay. When the battery automatically shuts down due to zero charge, please recharge immediately.

Supplied as standard with



GPU host



2M NATO cable



10A Charger

Optional extras









All HAWKER products come with a 1-year warranty on workmanship and materials. Batteries are cycle-dependent and therefore are not covered under this warranty. Batteries have no memory effect and can be recharged at anytime.

Hawker Aero International Limited

www.hawkeraero.com Email:sales@hawkeraero.com Agency