

HAWKER AERO

26V Portable Starting Units

Model 2879

The Hawker Aero GPU utilizes the newest technology in Lithium iron phosphate batteries. These LFP batteries have double the battery life of lead-acid batteries.

The modular design allows two GPUs to be paralleled to double the continuous output and battery capacity.

This portable GPU is a 26VDC battery pack, Each GPU is suitable for the aircraft which has the protection that no more than 28.6 volts. For example, **Pilatus pc6/pc12**.

Each GPU is suitable for the aircraft which has the protection that no more than 29.9 volts. For example, **AW139, Sikorsky S-76D**.



Specifications

- Peak current 5500A
- Max continuous amps 800A30S 400A400S
- Nominal voltage DC25.6V (24V-27.8V)
- Max voltage DC28.3V
- Amp/hour capacity 80Ah@10hr rate(20°C)
- Operating temp -20°C to +60°C(-4°F to +140°F)
- Case Aluminum, superficial static electricity spurts
- Aircraft cable 2m(6ft)with Nato connector
- Input voltage 90-240VAC 50/60HZ
- Input current 25A
- Dimensions H482L457W127mm(H19”L18”W5”in)
- Weight 26.5kgs(58lbs)
- Supplied with unit Charger(90-250VAC,50/60Hz),Aircraft cable

Safety, long lifetime, heavy current, light weight, and environment friendly.

PLEASE NOTE: Never run the batteries down below 23 volts,during a start is okay.
The batteries will be damaged below 20 volts.

Supplied as standard with



Optional extras



All Hawker Aero products come with a 1-year warranty on workmanship and materials.
The batteries are cycle-dependent and therefore are not covered under this warranty.

Hawker Aero International Limited

www.hawkaero.com

Email:sales@hawkaero.com

Agency